

# TOSHIBA

Leading Innovation >>>

**e-STUDIO2303A**

**e-STUDIO2303AM**

**e-STUDIO2803AM**

**e-STUDIO2309A**

**e-STUDIO2809A**

**Compact.  
Efficient.  
Economical.**



COPY



PRINT



A3



DUPLEX



COLOUR  
SCAN



COPY  
SPEED

**TOGETHER  
INFORMATION**

## Increased productivity

Offers a wide range of paper handling options to satisfy the varying needs of users.



## Colour Scan and Scan to USB

Besides having the capability of Colour Scan, users can also enjoy the convenience of scanning directly to USB drive.



## Department codes


Administrators can manage printing cost by tracking the print volume of departments and users, limiting unauthorised usage through this simple security management.



## Mobile Printing

Printing is even more hassle-free now! Simply connect and print directly from our mobile phone or tablet.

\*With PS option on e-STUDIO2309A/2809A



SPECIFICATION for	e-STUDIO2303A	e-STUDIO2303AM/2803AM	e-STUDIO2309A/2809A
<b>GENERAL</b>			
Copying/Printing Process	Indirect electrostatic photographic method		
Print & Copy Speed	23cpm	23/28cpm	
Warm-up Time	Approx. 18 seconds		
Paper Size & Weight	Drawer: A3/A5-R (64 - 80gsm) Stack Feed Bypass: A3/A5-R (52 - 216gsm)		
Paper Capacity	Drawer: 250 sheets Stack Feed Bypass: 100 sheets		
Max. Paper Capacity	600 sheets	1700 sheets	
Paper Exit	Face down/Inner exit (100 sheets)		
Processor	ARM9 360MHz	Cortex A8 500MHz	
Memory	512MB		
Dimensions	W575 x D540 x H402 (mm)		
Weight (Approx.)	27kg		
Power Consumption	1.5kW (220-240V)		
Operation Noise	64.75dB(A)		
Special Features	Auto Sleep Mode, Auto Energy Saver		
<b>COPY</b>			
Max. Original Size	A3		
Resolution	2400dpi x 600dpi (with smoothing)		
Multiple Copy Qty	1-999/Ten key input		
First Copy	Less than 6.4 seconds (A4 size from 1st drawer, 100%)		
Zoom	25% to 400% (1% Increment)		
Copy Mode	Text, Text/Photo(Default), Photo, Background Erase		
Image Density Control	Automatic / Manual ( 9 Steps )		
<b>PRINT</b>			
Resolution	2400dpi x 600dpi (with smoothing)		
Page Description Language	GDI	PCL6 (PCL.XL), PCL5e, PCL5c, PS (Option)	
Operating Systems	Windows Vista SP2 (32/64 bit) Windows 7 SP1 (32/64 bit) (SP1 Recommended) Windows 8/8.1 (32/64 bit) Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) N.A		
Interface	USB 2.0/Hi Speed	10/100 BaseT, USB 2.0/Hi Speed	
Network Protocol	N.A	TCP/IP (IP v4/IP v6) NetBIDS over TCP/IP	
Print Protocol	N.A	LPR/LPD, Port 9100 (bi-directional), IPP ver1.1	
Print Function	Toner Save Mode, Watermark, Multiple Pages Per Sheet		
<b>SCAN</b>			
Resolution	600 x 600dpi		
Scan Speed	Up to 25spm		
Scan Modes	B&W, Greyscale, Colour		
File Formats	B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page		
Scan Agent	Scan to USB, Remote TWAIN		Scan to USB, Remote TWAIN, Scan to File (SMB/FTP), Scan to Email
<b>FAX (OPTION)</b>			
Compatibility	N.A	Super G3, G3	
Data Compression Method	N.A	JBIG, MMR, MR, MH	
Modem Speed	N.A	33.6kbps - 2.4Kbps (Auto Fallback)	
Transmission Speed	N.A	Approx. 3 sec.	
Broadcast Transmission	N.A	Max. 32 Groups, 220 destinations per job	
<b>OPTIONS</b>			
Document Feeder (RADF)	MR-3029	✓	
Platen Cover	KA-2507PC	✓	
Paper Feed Unit	MY-1043	✓	
Desk	MH-2506	✓	
Harness Kit for Coin Controller	GQ-1131	✓	
Auto Duplex Unit	MD-0107	✓	N.A (Standard)
Paper Feed Pedestal	KD-1039	N.A	✓
Drawer Module	MY-1044	N.A	✓
FAX Kit	GD-1360	N.A	✓
Wireless LAN Module	GN-1080	N.A	✓
PS module + 1GB memory (es2309A)	GA-1340L	N.A	✓
PS module + 1GB memory (es2809A)	GA-1340H	N.A	✓

TSP Version 1.0

Distributed by

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION. All rights reserved. As an ENERGY STAR Partner, TOSHIBA TEC CORPORATION has determined that this multifunctional device model meets the ENERGY STAR guidelines for energy efficiency.

Driven by

